

KEQUM Series	
	KEQUM300
Chamber Temperature Range	Ambient +9°F (5°C) to 140°F (60°C)
Exterior Dimensions	45.3" x 39.4" x 78.7" 1150mm x 1000mm x 2000mm
Interior Dimensions	28" x 19.5" x 29.5 - 34.3" 710mm x 495mm x 750mm - 870mm
Lid Open Dimensions	45.3" x 64" x 78.7" 1150mm x 1620mm x 2000mm
Shipping Dimensions	72.8" x 47.2" x 49.2" 1850mm x 1200mm x 1250mm
Move-in Dimensions	76.8" x 51.2" x 53.1" 1950mm x 1300mm x 1350mm
Net Weight (Empty)	143 lbs. (65 kg)
Gross Weight (w/ shipping package)	309 lbs (140 kg)
Chamber Volume	79.3 gal (300 L)
Ambient Temperature Requirements	+75°F (+24°C) to +82°F (+28°C)
Ambient Humidity Requirements	max. 82% without condensation
Power	230V - 50-60Hz - 1 phase
FLA (230V)	10A
Water Quality	ASTM D1193 Type IV
Water Supply	7 to 28 psi (0.5 to 2.0 kgf/cm ²)
Water Connection	1/2" hose barb fitting
Water Usage	1.32 gal per day (5 liters)
Gravity Drains	1/2" hose barb fitting

